

TECHNICAL DATA

# Fluke 302+ CAT III Digital Clamp Meter







## Key features

- AC current measurements up to 400 A, handling your everyday electrical maintenance needs
- Comes with the TL75 Hard Point™ Test Lead Set offering the convenience of a test lead and probe in one unit with a variety of connections
- Rugged, easy-to-use digital clamp meter with CAT IV 300 V/CAT III 600 V safety rating

## Product overview: Fluke 302+ CAT III Digital Clamp Meter

The Fluke 302+ is a compact, easy-to-use digital clamp meter made to fit the way you work. It is the perfect first-pass troubleshooting tool: small enough to fit in a work bag, tough enough to withstand daily use, and extremely simple to use. All without compromising safety. For everyday applications, where True-RMS accuracy isn't needed, the Fluke 302+ delivers reliable measurements time after time.

### Fluke 302+ Additional Features

- The Fluke 302+ CAT III Digital Clamp Meter is more compact, making the use of clamp-type ammeter more flexible and simpler
- Measure AC current up to 400A
- 30 mm large jaw
- High accuracy of 1.8%
- Backlit display
- Two-year warranty

### Fluke 302+ Comes with Fluke TL75 Hard Point™ Test Lead Set

- One pair (red, black) of comfort grip probes
- 48 inches (1.22 meter) PVC insulated test leads with right-angle shrouded banana plugs
- Recommended for general purpose measurements
- CAT II 1000 V, 10 A rating
- CAT IV 600 V, CAT III 1000 V only with protective cap

### Fluke 302+ Safety Features

- Meets CAT IV 300V/CAT III 600V safety rating

## Specifications: Fluke 302+ CAT III Digital Clamp Meter

Technical Specifications		
AC current	<b>Range</b>	400.0 A
	Accuracy	1.8% u00b15
AC voltage	<b>Range</b>	400/600
	Accuracy	1.5% u00b15
DC voltage	<b>Range</b>	400/600
	Accuracy	1.5% u00b15
DC mV range		-
Resistance	<b>Range</b>	4000 u2126
	Accuracy	1% u00b15



Continuity		u2264 70 u2126
Backlight display		Yes
Data hold		Yes
Size	<b>H x W x D (mm)</b>	208 x 58.5 x 28
	Jaw size	30 mm
Safety rating		CAT III 600 V
Temperature		0 ~ 40 u00b0C
Screen refresh rate		> 2 times / sec.
Test leads		TL75
Baery		2 AAA baeries
Warranty		2 years

## Ordering information



### **FLUKE-302+**

Fluke 302+ Digital Clamp Meter

Includes:

- Fluke 302+ Digital Clamp Meter
- Fluke TL75 Test Leads
- 2 AA Batteries

<b>Optional accessories</b>	<b>Description</b>
<b>Fluke TL175 TwistGuard™ Test Leads</b>	Simply twist to change the exposed probe tip length.
<b>Fluke AC175 Alligator Clip Set</b>	Extended capability for your test leads with a 7mm jaw opening.
<b>Fluke TL75 Hard Point™ Test Lead Set</b>	PVC-insulated, right-angle shrouded 4 mm (0.16 in) banana plugs



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2024 Fluke Corporation.  
Specifications subject to change without notice.  
10/2024

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**