

TECHNICAL DATA

# Fluke 154 HART Calibration Assistant



## FLUKE 154 FEATURES


- Full HART Device Description (DD) support of all HART devices
- Configure HART devices
- Perform HART trim on hart devices when used with a Fluke 750, or 720 series calibrator
- Monitor device PV, SV, TV, QV and other measured HART variables
- Convenient wireless connectivity to HART modem
- Easy to use, fast connect and view HART data
- Store HART device configurations
- Long range wireless communication up to 250 feet

**“HART Calibration assistance at your fingertips”**

**Combine with a Fluke calibrator for a total HART calibration solution.**

The Fluke 154 is a standalone tablet based HART® communication tool. The tablet configured with the “FlukeHART” mobile app utilizes a wireless HART modem that connects directly to the HART transmitter being tested or configured. When you combine your Fluke 154 HART Calibration Assistant with a Fluke 750 Series Documenting Process Calibrator, or a 720 Series Multifunction Process Calibrator you have a complete HART calibration and configuration solution.

The 154 puts HART device configuration at your fingertips. An Android™ based tablet user interface makes HART configuration easy. The external wireless modem allows you to connect the modem to the transmitter being tested so you can communicate to the device remotely. HART transmitters can often be found in confined spaces that are difficult to access, or are out of reach. The Fluke 154 helps reduce the need to stand right next to the device being tested or configured so you can work from a safer, more convenient location.



## Specifications

<b>Key features</b>		<b>Tablet</b>
Operating system		Android 5.0 or newer
Processor		ARM or Atom
Memory RAM		1 GB
Memory ROM		2 GB
Screen		960x540 qHD
Communication port		Bluetooth
<b>Key features</b>		<b>HART modem</b>
<b>Enclosure</b>		
Material		High strength ABS Plastic
Dimensions (LxWxH)		10.16 cm x 2.5 cm x 6.9 cm (4 in x 1 in x 2.75 in)
Total unit weight		.16 kg (0.36 lb)
<b>Cables</b>		
HART cable length		4 ft (1.2 m)
HART cable connectors		Mini-Grabber
<b>HART interface</b>		
Interface		Capacitive coupling
Output		600 mVpp
Leakage		< 10 uA
Connections		Across loop resistor or HART field device
Specifications		HART 4, HART 5, HART 6, HART 7
HART physical layer spec		HCF_SPEC-54
<b>Wireless interface</b>		
Specification		Bluetooth v2.0
Frequency		2.4 GHz
Class 1 master distance		275 ft (83.8 m)
<b>Battery</b>		
Type		Rechargeable Li-Ion
Life		19 hours continuous use
<b>Environmental</b>		
Operating temperature		0 °C to 50 °C (32 °F to 122 °F)
Storage temperature		-10 °C to 45 °C (-14 °F to 113 °F)
Humidity		0 % to 90 % (non-condensing)

**Multiple language support**

Select language from the Android operating system. Hart communication commands are limited to English per the HART device descriptions.

**Wireless HART Modem**

Includes configurable connection cable that accepts either the hook clips for connecting to wires or the extended tooth alligator clips designed to connect to transmitter connection screw heads. Rechargeable lithium-ion battery lasts easily for several days of HART device configuration and testing activities. Rugged enclosure and test lead set designed for process environments

**Store device configurations**

Store HART device configurations in ASCII or PDF file configurations.

**HART support**

Complete access to all features of the HART device's DD including methods. Meets HART physical layer specification: HCF\_SPEC-54

**Hard side case**

Protects and stores tablet, modem, test leads and connection cable in a lightweight durable tote that is easy to carry.



**Ordering information**

**Fluke-154** HART Calibration Assistant

**Included**

Tablet, tablet charger and USB micro-cable, Fluke HART App. (installed), HART modem, USB mini-cable, proof of purchase for product activation, hook test clips, alligator clips, magnetic hanging strap, and case. Manual installed on tablet. Three-year warranty.

**Fluke.** *Keeping your world up and running.*®

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2016, 2020 Fluke Corporation.  
Specifications subject to change without notice.  
07/2020 6007081c-en

**Modification of this document is not permitted without written permission from Fluke Corporation.**